

IN THE CLAIMS

Please amend the claims as follows:

Claims 1-9 (Canceled).

Claim 10 (Currently amended): A process for obtaining crude 1,3-butadiene  
comprising:

~~by extractive distillation~~ extractively distilling with a selective solvent the crude 1,3-  
butadiene in a dividing wall column from a C<sub>4</sub> cut comprising C<sub>4</sub> acetylenes as secondary  
components; ~~in a dividing wall column having a bottom evaporator, in which a dividing wall~~  
~~is disposed in the longitudinal direction of the column to form a first subregion, a second~~  
~~subregion and a lower combined column region, and which is disposed upstream of an~~  
~~extractive wash column;~~

~~which comprises controlling the energy input into the dividing wall column via the~~  
~~bottom evaporator in such a way that~~ to obtain a bottom stream comprising solvent, C<sub>4</sub>  
acetylenes and an economically acceptable proportion of 1,3-butadiene which is drawn off  
from the dividing wall column; ~~and comprises solvent laden with the C<sub>4</sub>-acetylenes whose~~  
~~proportion of 1,3-butadiene is restricted such that the loss of 1,3-butadiene is economically~~  
~~acceptable, and~~

feeding the bottom stream to an acetylenes outgasser; ~~and, in the acetylenes outgasser,~~  
wherein stripping out the C<sub>4</sub> acetylenes are stripped out overhead and ~~obtaining~~ purified  
solvent is obtained as ~~[[the]]~~ a bottom stream;

wherein

the dividing wall column comprises a bottom evaporator,

a dividing wall is disposed in the longitudinal direction of the dividing wall column to form a first subregion, a second subregion and a lower combined column region having one or more separation stages, and

the dividing wall column is disposed upstream of an extractive wash column.

Claim 11 (Currently Amended): The process according to claim 10, wherein the economically acceptable proportion of 1,3-butadiene in the bottom stream of the dividing wall column is ~~restricted to a maximum~~ in a range of from 0.1 to 2 times the proportion of C<sub>4</sub> acetylenes in the bottom stream of the dividing wall column.

Claim 12 (Currently Amended): The process according to claim 11, wherein the economically acceptable proportion of 1,3-butadiene in the bottom stream of the dividing wall column is ~~restricted to~~ 0.3 times the proportion of C<sub>4</sub> acetylenes in the bottom stream of the dividing wall column.

Claim 13 (Currently Amended): The process according to claim 10, ~~wherein the~~ further comprising:

utilizing energy of the bottom stream of the dividing wall column ~~is utilized~~ for indirect heat exchange with the bottom stream of the acetylenes ~~degasser~~ outgasser and/or with ~~[[the]]~~ liquid which is drawn off from the one or more separation stages in the lower combined column region ~~[[C]]~~ of the dividing wall column, and

selecting the one or more separation stages ~~stage~~ from which the liquid is drawn off is ~~selected in such a way that~~ to minimize the energy demand for the dividing wall column ~~is~~ minimal.

Claim 14 (Currently Amended): The process according to claim 10, ~~wherein the~~  
further comprising:

utilizing a heat content of the bottom stream of the acetylenes outgasser ~~is utilized~~ for indirect heat exchange with the liquid which is drawn off from one or more separation stages in the lower combined column region of the dividing wall column, and

determining the separation stage(s) from which the liquid is drawn off ~~is/are~~  
~~determined in such a way that~~ to minimize the energy demand for the dividing wall column ~~is~~  
~~minimal~~, and/or

utilizing that the heat content of the bottom stream ~~is utilized~~ for indirect heat exchange with ~~[[the]]~~ a C<sub>4</sub> cut to be separated ~~which is~~ and fed to the dividing wall column.

Claim 15 (Currently Amended): ~~The process according to claim 10,~~ A process for  
obtaining crude 1,3-butadiene comprising:

extractively distilling with a selective solvent the crude 1,3-butadiene in thermally  
coupled columns from a C<sub>4</sub> cut comprising C<sub>4</sub> acetylenes as secondary components;

controlling the energy input into the thermally coupled columns to obtain a bottom  
stream comprising solvent, C<sub>4</sub> acetylenes and an economically acceptable proportion of 1,3-  
butadiene which is drawn off from the thermally coupled columns;

feeding the bottom stream to an acetylenes outgasser; wherein the C<sub>4</sub> acetylenes are  
stripped out overhead and purified solvent is obtained as the bottom stream.

~~wherein thermally coupled columns are used instead of the dividing wall column.~~

Claim 16 (Currently Amended): The process according to claim 10, wherein  
the C<sub>4</sub> cut is fed to the first subregion of the dividing wall column,

the top stream from the first subregion of the dividing wall column is fed to a lower region of the extractive wash column, ~~into its lower region,~~

in the extractive wash column, a countercurrent extraction is carried out by charging with a first substream of the selective solvent in the upper region of the extractive wash column,

the components of the C<sub>4</sub> cuts having lower solubility than 1,3-butadiene in the selective solvent are drawn off via the top of the extractive wash column,

the bottom stream from the extractive wash column is recycled into the upper region of the first subregion of the dividing wall column,

second substream of the selective solvent is fed to the dividing wall column in the upper region of the second subregion,

the top product from the second subregion of the dividing wall column is drawn off as crude 1,3-butadiene and

a bottom stream ~~consisting of~~ comprising solvent, ~~laden with~~ the C<sub>4</sub> acetylenes, and an economically acceptable ~~whose proportion of 1,3-butadiene is restricted such that the loss of 1,3-butadiene is economically acceptable,~~ is drawn off from the lower combined column region of the dividing wall column,

the bottom stream is fed to the acetylenes ~~degasser~~ outgasser in which the C<sub>4</sub> acetylenes are stripped out overhead and purified solvent ~~[[is]]~~ obtained as the bottom stream ~~and~~ is recycled into the process.

Claim 17 (Currently Amended): The process according to claim 10, wherein ~~[[the]]~~ a temperature in the bottom evaporator of the dividing wall column is ~~controlled to a value~~ in the range from 50 to 210°C, ~~and the~~

a top pressure of the second subregion of the dividing wall column ~~to a value~~ is in the range from 1 to 10 bar absolute and

[[the]] a top pressure in the acetylenes outgasser ~~to a value~~ is in the range from 1 bar absolute to a maximum of the bottom pressure in the dividing wall column.

Claim 18 (Currently Amended): The process according to claim 10, wherein the acetylenes outgasser is integrated by construction into the lower combined column region by configuring the number of theoretical plates in the lower combined column region to a correspondingly larger value and incorporating a gas-tight division in the dividing wall column at [[the]] a point which corresponds to the upper end of the acetylenes outgasser integrated into the lower combined column region.

Claim 19 (Currently Amended): The process according to claim 17, wherein the temperature in the bottom evaporator of the dividing wall column is ~~controlled to~~ 178°C, and the top pressure of the second subregion of the dividing wall column ~~to a value~~ is in the range from 2 to 5 bar absolute.

Claim 20 (Currently Amended): The process according to claim 19, wherein the top pressure of the second subregion of the dividing wall column is ~~controlled to~~ 3.5 bar absolute.

Claim 21 (Previously presented): The process according to claim 16, wherein the C<sub>4</sub> cut is fed into the middle region of the first subregion of the dividing wall column.